



MATERIAL SAFETY DATA SHEET

Section 1 - Product and Company Identification

Product Name:	Agilent HC-C18 Chromatography Column			
Agilent Part Number:	518905-902			
Date Prepared:	12/01/05	Number o	of Pages:	3
Supplier's Name:	Agilent Technologies, Inc.			
	Logistics Center - Americas			
	500 Ships Landing Way			
	New Castle, Delaware 19720			
USA Information Telephone Number:	1-302-633-8777			
USA Emergency Telephone Number:	1-877-4Agilent			
When calling from outside the USA	dial your International Access Code for the USA	then 1	then 302	-

When calling from outside the USA, dial your International Access Code for the USA, then 1, then 302-633-8777

Section 2 - Composition/Information on Ingredients

A 4.6 x 250 mm chromatography column containing 5µm particle size packing material made by chemically bonding chlorodiisobutyloctadecylsilane with high purity amorphous silica [112926-00-8]. No CAS number exists for this product. Chemical Families: Surface modified amorphous silica

Chemical Synonyms: Amorphous silica is also known as Silica gel and precipitated silica.

Section 3 - Hazards Identification

May cause eye irritation. Do not breathe dust.

Section 4 - First-Aid Measures

Inhalation: Symptoms of overexposure may include cough and discomfort. If large amounts are inhaled, move affected person to fresh air. If breathing is difficult give oxygen. If breathing has stopped begin resuscitation measures. Contact physician.

Skin Contact: Wash with soap and water.

Eye Contact: May be a mild eye irritant. Contamination of the eyes should be treated by immediate and prolonged irrigation with copious amounts of water by separating the eyelids with fingers. If redness or discomfort persists, contact a physician.

Ingestion: This compound is not likely to be hazardous by ingestion. However, if swallowed, wash out mouth with water provided affected person is conscious. Consult a physician.

Section 5 - Fire-Fighting Measures

Extinguishing Media: Appropriate to surroundings **Special Fire Fighting Procedures**: Wear full protective clothing and self contained positive pressure breathing apparatus certified by NIOSH when fighting chemically related fires. **Unusual Fire and Explosion Hazards**: Small amounts of flammable vapor may be produced if heated to approximately 500°F.

Section 6 - Accidental Release Measures

Wearing appropriate personal protective equipment, shovel or sweep up using a dust suppresser. Vacuum the remainder of the smaller quantities using a HEPA-type vacuum. Avoid inhaling dust. Place waste in a plastic bag or other suitable container and dispose of as residual waste. This material is not defined as hazardous waste by RCRA (40 CFR Part 261) and may be landfilled according to federal, state and local regulations.

<u>DISCLAIMER</u>: This Safety Data Sheet is offered without charge to the clients of Agilent Technologies. Data is the most current available to Agilent Technologies at the time of preparation and is issued as a matter of information only; no warranty as to its accuracy or completeness is expressed or implied.

Agilent Technologies

<u>Section 7 - Handling and Storage</u>

Do not breathe dust and avoid contact with skin and eyes. Wash thoroughly after handling. Maintain good housekeeping practices. Avoid creating dust. Keep containers closed. Do not store with incompatible materials. Store in a cool, dry place.

Section 8 - Exposure Controls/Personal Protection

Ventilation: Adequate ventilation is required to protect personnel from exposure to chemical vapors or dusts exceeding PEL and to minimize fire hazards. See Section 15 for regulatory standards of exposure.

Respiratory: Use NIOSH approved respirator equipment. See Section 15.

Eyes: Safety glasses are considered minimum protection. Chemical safety goggles or face shield may be necessary depending on quantity of material and conditions of use. Emergency eye wash fountains should be available in the vicinity of any possible exposure.

Skin: Chemical-resistant protective gloves and clothing are recommended. The choice of protective gloves or clothing must be based on chemical resistance and other user requirements. Generally BUNA-N offers acceptable chemical resistance. Individuals who are acutely and specifically sensitive to this chemical may require additional protective clothing.

Section 9 - Physical and Chemical Properties

Flash Point (Method Used): NAExplosion Potential: LEL (NA)/UEL (NA)Specific Gravity (H20 = 1): NDMelting Point (Degree C): Decomposes above approximately 250°C (500°F)Evaporation Rate (n-butyl acetate =1) NABoiling Point (Degree C): NDVapor Pressure (mm Hg at 25°C): NDVapor Density (Air =1): NAOdor Threshold: NDOctanol/Water Partition Coefficient: NASolubility in Water: Insoluble (X) /Soluble ()Appearance and Odor: White/off-white powder, faint odor

Section 10 - Stability and Reactivity

Stability: Stable (x) / Unstable ()
Conditions to Avoid: NA
Incompatibility (Materials to Avoid): Reacts with hydrofluoric acid (HF)
Hazardous Decomposition or Byproducts: NA
Hazardous Polymerization: May Occur () / Will Not Occur (x)

Section 11 - Toxicological Information

Route(s) of Entry: Inhalation? Yes Skin? No Ingestion? Yes May be harmful if inhaled or swallowed.

Health Hazard Acute/Chronic: This product does not contain crystalline silica (CA), which is considered hazardous by inhalation.

Carcinogenicity: NTP? No IARC Monographs? No OSHA Regulated? No OTHER? No Medical Conditions Generally Aggravated by Exposure: Preclude from exposure to dust those persons with preexisting upper respiratory and lung disease such as, but not limited to, bronchitis, emphysema and asthma.

Section 12 - Ecological Information

Persistence/Degradability: Based on chemical experience, will degrade over very long periods of time. Biodegradability: Will not biodegrade Bioaccumulation: NA

Section 13 - Disposal Considerations

Wastes are not hazardous as defined by RCRA (40 CFR Part 261). This material may be landfilled as a residual waste according to federal, state and local regulations.



Section 14 - Transport Information

DOT Regulations:	IATA-DGR Regulations:		
Shipping Name:	Non-regulated Material	Shipping Name:	Non-regulated Material
RID/ADR: NA	ADNR: NA		

Section 15 - Regulatory Information

Exposure Limits: There are no established exposure limits for this product-however if dust is generated by grinding or other means the following standard would apply: *Particulate Matter Not Otherwise Classified: (PNOC)*

OSHA PEL: 5 mg/m3 (Respirable fraction) 15 mg/m3 (Total dust)

ACGIH TWA: 3 mg/m3 (Respirable particulate) 10 mg/m3 (Inhalable particulate)

SARA Reporting: Section 302: None Section 304: None Section 313: None

OSHA Labeling Requirements: None

Section 16 - Other Information

Unless otherwise noted, the above information pertains only for the base material and similar types of components in the sample. When no toxicity data is provided, it is prudent to handle this chemical as hazardous. Furthermore, since individual chemical hypersensitivity cannot be predicted, every chemical should be handled with due respect.

KEY TO ABBREVIATIONS

ACGIH - American Conference of Governmental Industrial Hygienists` ADNR - Regulations concerning the carriage of dangerous goods on the Rhine CAS - Chemical Abstract Service DOT - US Department of Transportation 49 Code of Federal Regulations IARC - International Agency for Research on Cancer IATA-DGR - International Air Transport Association- Dangerous Goods Regulation LEL - Lower Explosion Limit NA - Not Applicable ND - No Data NIOSH - National Institute for Occupational Safety and Health NTP - National Toxicology Program OSHA - Occupational Safety and Health Administration PEL - Permissible Exposure Limit

RID/ADR - Regulations Concerning the International Carriage of Dangerous Goods by Rail/European Agreement Concerning the International Carriage of Dangerous Goods by Road **TLV** -Threshold Limit Value **TWA** - Time Weighted Average **UEL** - Upper Explosion Limit [] - Indicates CAS Number