Conforms to US OSHA Hazard Communication 29CFR1910.1200

SAFETY DATA SHEET



Eclipse AAA Chromatography Columns with Methanol and Water less than 10mL Solvent

Section 1. Identification

This product is considered an article. This Safety Data Sheet is written based on the encapsulated substance or mixture in this article.

| 1.1 Product identifier | | | |
|---|--|--|--|
| Product name | : Eclipse AAA Chromatography Columns with Methanol and Water less than 10mL Solvent | | |
| Part no. | : 961400-302, 966400-902, 963400-902, 993400-902 | | |
| Validation date | : 11/20/2020 | | |
| 1.2 Relevant identified uses of the substance or mixture and uses advised against | | | |
| Material uses | : Analytical chemistry. HPLC column Solvent Volume: <10mL 961400-302 Eclipse AAA, 3.0 x 150 mm, 3.5 micron 966400-902 Eclipse AAA 4.6 x 75mm 3.5um 963400-902 Eclipse AAA 4.6 x 150mm 3.5um 993400-902 Eclipse AAA 4.6 x 150mm 5um | | |
| 1.3 Details of the supplier | of the safety data sheet | | |

| Supplier/Manufacturer | : Agilent Technologies, Inc. 5301 Stevens Creek Blvd Santa Clara, CA 95051, USA 800-227-9770 |
|-----------------------|---|
| | 800-227-9770 |

1.4 Emergency telephone number

In case of emergency : CHEMTREC®: 1-800-424-9300

Section 2. Hazards identification

This article, when used under reasonable conditions and in accordance with the directions for use, should not present a health hazard. The substance or mixture is encapsulated in the article. Only if released due to use or processing of the article in a manner not in accordance with the product's directions for use it may present potential health and safety hazards.

2.1 Classification of the substance or mixture

| OSHA/HCS status | : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). | | | |
|-------------------------------|---|--|--|--|
| Classification of the substar | Classification of the substance or mixture | | | |
| H225 | FLAMMABLE LIQUIDS - Category 2 | | | |
| H302 | ACUTE TOXICITY (oral) - Category 4 | | | |
| H312 | ACUTE TOXICITY (dermal) - Category 4 | | | |
| H332 | ACUTE TOXICITY (inhalation) - Category 4 | | | |
| H315 | SKIN IRRITATION - Category 2 | | | |
| H319 | EYE IRRITATION - Category 2A | | | |
| H360 | TOXIC TO REPRODUCTION - Category 1B | | | |
| H370 | SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1 | | | |
| H335 | SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract | | | |
| | irritation) - Category 3 | | | |
| H336 | SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - | | | |
| | Category 3 | | | |

Section 2. Hazards identification

2.2 GHS label elements Hazard pictograms Signal word Danger **Hazard statements** : H225 - Highly flammable liquid and vapor. H302 + H312 + H332 - Harmful if swallowed, in contact with skin or if inhaled. H315 - Causes skin irritation. H319 - Causes serious eye irritation. H335 - May cause respiratory irritation. H336 - May cause drowsiness or dizziness. H360 - May damage fertility or the unborn child. H370 - Causes damage to organs. (central nervous system (CNS), optic nerve) **Precautionary statements Prevention** : P201 - Obtain special instructions before use. P280 - Wear protective gloves, protective clothing and eye or face protection. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. : P308 + P311 - IF exposed: Call a POISON CENTER or doctor. Response : P403 + P235 - Store in a well-ventilated place. Keep cool. Storage Disposal : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations. 2.3 Other hazards Hazards not otherwise : None known. classified

Section 3. Composition/information on ingredients

This article, when used under reasonable conditions and in accordance with the directions for use, should not present a health hazard. The substance or mixture is encapsulated in the article. Only if released due to use or processing of the article in a manner not in accordance with the product's directions for use it may present potential health and safety hazards.

Substance/mixture

: Mixture (encapsulated in article)

| Ingredient name | % | CAS number |
|-----------------|-----------|------------|
| Methanol | ≥25 - <30 | 67-56-1 |

Contains : Organosilane bonded silica gel

Note: To the best of our knowledge, the acute and chronic toxicological properties of bonded silica gels have not been investigated. This product contains synthetic amorphous silica, and should not be confused with crystalline silica such as quartz, cristobalite, or tridymite, or with diatomaceous earth or other naturally occurring forms of amorphous silica that frequently contain crystalline forms of silica.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

| 4.1 Description of nece | ssary first aid measures |
|-------------------------|--|
| Eye contact | Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician. |
| Inhalation | : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. |
| Skin contact | : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician. Wash clothing before reuse. Clean shoes thoroughly before reuse. |
| Ingestion | : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. |

4.2 Most important symptoms/effects, acute and delayed

| Potential acute health effect | S | |
|-------------------------------|----|---|
| Eye contact | : | Causes serious eye irritation. |
| Inhalation | : | Harmful if inhaled. Causes damage to organs following a single exposure if inhaled. Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation. |
| Skin contact | 1 | Harmful in contact with skin. Causes damage to organs following a single exposure in contact with skin. Causes skin irritation. |
| Ingestion | : | Harmful if swallowed. Causes damage to organs following a single exposure if swallowed. Can cause central nervous system (CNS) depression. |
| Over-exposure signs/sympt | om | <u>IS</u> |
| Eye contact | : | Adverse symptoms may include the following: pain or irritation watering redness |
| Inhalation | : | Adverse symptoms may include the following: respiratory tract irritation coughing nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness reduced fetal weight increase in fetal deaths skeletal malformations |

Section 4. First aid measures

| Skin contact | : Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations |
|----------------------------|---|
| Ingestion | : Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations medical attention and special treatment needed, if necessary |
| Notes to physician | Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. |
| Specific treatments | : No specific treatment. |
| Protection of first-aiders | : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or |

See toxicological information (Section 11)

Section 5. Fire-fighting measures

| 5.1 Extinguishing media | |
|--|--|
| Suitable extinguishing media | : Use dry chemical, CO ₂ , water spray (fog) or foam. |
| Unsuitable extinguishing media | : Do not use water jet. |
| 5.2 Special hazards arising f | rom the substance or mixture |
| Specific hazards arising from the chemical | : Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. |
| Hazardous thermal decomposition products | : Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides Formaldehyde. |
| 5.3 Advice for firefighters | |
| Special protective actions for fire-fighters | : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. |
| Special protective equipment for fire-fighters | : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. |

Section 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

| For non-emergency personnel | : | No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. |
|--------------------------------|-----|---|
| For emergency responders | : | If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". |
| 6.2 Environmental precautions | : | Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). |
| 6.3 Methods and materials fo | r c | ontainment and cleaning up |

Methods for cleaning up : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

7.1 Precautions for safe handling

| Protective measures | : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container. |
|--|---|
| Advice on general occupational hygiene | : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. |
| 7.2 Conditions for safe storage, including any incompatibilities | : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use. |
| 7.3 Specific end use(s) Recommendations | : Industrial applications, Professional applications. |

Section 7. Handling and storage

Industrial sector specific : Not available. solutions

Section 8. Exposure controls/personal protection

Since the hazardous ingredient in this article is encapsulated, the risk of exposure by inhalation, ingestion, skin contact and eyes contact is minimum.

8.1 Control parameters

Occupational exposure limits

| Ingredient name | Exposure limits |
|-----------------|--|
| Methanol | ACGIH TLV (United States, 3/2019). Absorbed through skin. TWA: 200 ppm 8 hours. TWA: 262 mg/m ³ 8 hours. STEL: 250 ppm 15 minutes. STEL: 328 mg/m ³ 15 minutes. OSHA PEL 1989 (United States, 3/1989). Absorbed through skin. TWA: 200 ppm 8 hours. TWA: 260 mg/m ³ 8 hours. STEL: 250 ppm 15 minutes. STEL: 325 mg/m ³ 15 minutes. |
| | NIOSH REL (United States, 10/2016). Absorbed through skin. TWA: 200 ppm 10 hours. TWA: 260 mg/m ³ 10 hours. STEL: 250 ppm 15 minutes. STEL: 325 mg/m ³ 15 minutes. OSHA PEL (United States, 5/2018). TWA: 200 ppm 8 hours. TWA: 260 mg/m ³ 8 hours. |

| 8.2 Exposure control | | |
|---------------------------------|---|-----|
| Appropriate engineer controls | Ise only with adequate ventilation. Use process enclosures, local exhaust ventilation other engineering controls to keep worker exposure to airborne contaminants below a recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment. | |
| Environmental expos controls | : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. | |
| Individual protection | neasures | |
| Hygiene measures | Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. | ý |
| Eye/face protection | : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles. | |
| | | |
| Date of issue : | 1/20/2020 6/ | /14 |

Section 8. Exposure controls/personal protection

| Hand protection | : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. |
|------------------------|--|
| Body protection | : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear antistatic protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. |
| Other skin protection | : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| Respiratory protection | : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. |

Section 9. Physical and chemical properties

| 9.1 Information on basic phys | sic | al and chemical properties |
|--|-----|--|
| <u>Appearance</u> | | |
| Physical state | 1 | Solid. (containing flammable liquid) |
| Color | 1 | Not available. |
| Odor | 1 | Not available. |
| Odor threshold | 1 | Not available. |
| рН | 1 | Not available. |
| Melting point | 1 | Not available. |
| Boiling point | : | Not available. |
| Flash point | : | Closed cup: -18 to 23°C (-0.4 to 73.4°F) |
| Evaporation rate | 1 | Not available. |
| Flammability (solid, gas) | 1 | Contains: Flammable liquid |
| Lower and upper explosive (flammable) limits | : | Not available. |
| Vapor pressure | 1 | Not available. |
| Vapor density | 1 | Not available. |
| Relative density | 1 | Not available. |
| Solubility | : | Mobile phase: Soluble Stationary phase: Insoluble |
| Partition coefficient: n- octanol/water | : | Not available. |
| Auto-ignition temperature | : | Not available. |
| Decomposition temperature | : | Not available. |
| Viscosity | 1 | Not available. |

Section 10. Stability and reactivity

| | , <u> </u> | |
|--|---|------|
| 10.1 Reactivity | No specific test data related to reactivity available for this product or its ingredients. | |
| 10.2 Chemical stability | The product is stable. | |
| 10.3 Possibility of hazardous reactions | Under normal conditions of storage and use, hazardous reactions will not occur. | |
| 10.4 Conditions to avoid | Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. | |
| 10.5 Incompatible materials | Reactive or incompatible with the following materials: oxidizing materials Incompatible with hydrogen fluoride. | |
| 10.6 Hazardous decomposition products | Under normal conditions of storage and use, hazardous decomposition products sh not be produced. | ould |

Section 11. Toxicological information

11.1 Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|-------------------------|-----------------------|---------|-------------|----------|
| Methanol | LC50 Inhalation Vapor | Rat | 189.95 mg/l | 1 hours |
| | LC50 Inhalation Vapor | Rat | 145000 ppm | 1 hours |
| | LC50 Inhalation Vapor | Rat | 83.84 mg/l | 4 hours |
| | LC50 Inhalation Vapor | Rat | 64000 ppm | 4 hours |
| | LD50 Dermal | Rabbit | 15800 mg/kg | - |
| | LD50 Oral | Rat | 5600 mg/kg | - |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|-------------------------|--|------------------|-------|----------------------------|-------------|
| Methanol | Eyes - Moderate irritant | Rabbit | - | 24 hours 100 | - |
| | Eyes - Moderate irritant Skin - Moderate irritant | Rabbit Rabbit | - | mg 40 mg 24 hours 20 | - |
| | Skin - Moderale Imlant | Raddil | - | mg | - |

Conclusion/Summary

: Repeated exposure may cause skin dryness or cracking.

Sensitization

Skin

Not available.

| Mutagenicity | |
|-----------------------------|-------------------------------|
| Conclusion/Summary | : Not available. |
| Carcinogenicity | |
| Conclusion/Summary | : Not available. |
| Reproductive toxicity | |
| Conclusion/Summary | : Not available. |
| Teratogenicity | |
| Conclusion/Summary | : Not available. |
| Specific target organ toxic | <u>city (single exposure)</u> |

Section 11. Toxicological information

| Name | Category | Route of exposure | Target organs | |
|----------|------------|-------------------|---|--|
| Methanol | Category 1 | - | central nervous system (CNS), optic nerve | |
| | Category 3 | | Respiratory tract irritation | |
| | Category 3 | | Narcotic effects | |

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

| nformation on the likely outes of exposure | : Routes of entry anticipated: Oral, Dermal, Inhalation. |
|---|---|
| Potential acute health effects | 2 |
| Eye contact | : Causes serious eye irritation. |
| Inhalation | : Harmful if inhaled. Causes damage to organs following a single exposure if inhaled. Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation. |
| Skin contact | : Harmful in contact with skin. Causes damage to organs following a single exposure in contact with skin. Causes skin irritation. |
| Ingestion | : Harmful if swallowed. Causes damage to organs following a single exposure if swallowed. Can cause central nervous system (CNS) depression. |
| | vsical, chemical and toxicological characteristics |
| Eye contact | : Adverse symptoms may include the following: pain or irritation watering redness |
| Inhalation | : Adverse symptoms may include the following: respiratory tract irritation coughing nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness reduced fetal weight increase in fetal deaths skeletal malformations |
| Skin contact | : Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations |
| Ingestion | : Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations |

Section 11. Toxicological information

Delayed and immediate effects and also chronic effects from short and long term exposure

| Short term exposure | |
|-------------------------------|---|
| Potential immediate effects | : Not available. |
| Potential delayed effects | : Not available. |
| <u>Long term exposure</u> | |
| Potential immediate effects | : Not available. |
| Potential delayed effects | : Not available. |
| Potential chronic health effe | <u>cts</u> |
| General | : No known significant effects or critical hazards. |
| Carcinogenicity | : No known significant effects or critical hazards. |
| Mutagenicity | : No known significant effects or critical hazards. |
| Reproductive toxicity | : May damage fertility or the unborn child. |

Numerical measures of toxicity

Acute toxicity estimates

| Product/ingredient name | Oral (mg/ kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | (vapors) | Inhalation (dusts and mists) (mg/ I) |
|--|------------------|-------------------|--------------------------------|-----------|---|
| Eclipse AAA Chromatography Columns with Methanol and Water less than 10mL Solvent Methanol | 362.3 100 | 1087 300 | N/A N/A | 10.9 3 | N/A N/A |

Other information

: Adverse symptoms may include the following: blurred or double vision, Eye contact can result in corneal damage or blindness. Repeated or prolonged exposure to the substance can produce liver damage.

Section 12. Ecological information

12.1 Toxicity

| Product/ingredient name | Result | Species | Exposure |
|-------------------------|--|--|----------------------|
| Methanol | Acute LC50 2500000 µg/l Marine water | Crustaceans - Crangon crangon - Adult | 48 hours |
| | Acute LC50 3289 mg/l Fresh water | Daphnia - Daphnia magna - Neonate | 48 hours |
| | Acute LC50 290 mg/l Fresh water Chronic NOEC 9.96 mg/l Marine water | Fish - Danio rerio - Egg Algae - Ulva pertusa | 96 hours 96 hours |

12.2 Persistence and degradability

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|-------------------------|-------------------|------------|------------------|
| Methanol | - | - | Readily |

12.3 Bioaccumulative potential

| Product/ingredient name | LogPow | BCF | Potential |
|-------------------------|--------|-----|-----------|
| Methanol | -0.77 | <10 | low |

| Date of issue : | 11/20/2020 | 10/ | /14 |
|-----------------|------------|-----|-----|
|-----------------|------------|-----|-----|

Section 12. Ecological information

12.4 Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

12.5 Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

| 13.1 Waste treatment methods | |
|------------------------------|---|
| Disposal methods : | The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. |

United States - RCRA Toxic hazardous waste "U" List

| Ingredient | CAS # | | Reference number |
|----------------------------------|---------|--------|---------------------|
| Methanol (I); Methyl alcohol (I) | 67-56-1 | Listed | U154 |

Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.

The information presented below only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

Section 14. Transport information

This Safety Data Sheet is written based on the encapsulated substance or mixture in this article. Since the hazardous ingredient is encapsulated, the risk of exposure by inhalation, ingestion, skin contact and eyes contact is minimum.

DOT / TDG / Mexico / IMDG / : Not regulated. IATA

Additional information

Remarks : Special provisions DOT: 47 TDG: 56 MX: 216 IATA: A46 IMDG: 216

Section 14. Transport information

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to IMO instruments

Section 15. Regulatory information

| 15.1 Safety, health and envir | onmental regulations/legislation specific for the substance or mixture |
|---|---|
| U.S. Federal regulations | : TSCA 8(a) CDR Exempt/Partial exemption: Not determined |
| Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs) | : Listed |
| Clean Air Act Section 602 Class I Substances | : Not listed |
| Clean Air Act Section 602 Class II Substances | : Not listed |
| DEA List I Chemicals (Precursor Chemicals) | : Not listed |
| DEA List II Chemicals (Essential Chemicals) | : Not listed |
| <u>SARA 302/304</u> | |
| Composition/information | on ingredients |
| No products were found. | |
| SARA 304 RQ | : Not applicable. |
| <u>SARA 311/312</u> | |
| Classification | FLAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (dermal) - Category 4 ACUTE TOXICITY (inhalation) - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A TOXIC TO REPRODUCTION - Category 1B SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 |

Composition/information on ingredients

| Name | % | Classification |
|--|------------------------|---|
| Organosilane bonded silica gel Methanol | ≥50 - ≤75 ≥25 - <30 | COMBUSTIBLE DUSTS FLAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY (oral) - Category 3 ACUTE TOXICITY (dermal) - Category 3 ACUTE TOXICITY (inhalation) - Category 3 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A TOXIC TO REPRODUCTION - Category 1B SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - |

Section 15. Regulatory information

Category 3

| <u>SARA 313</u> | | | |
|---------------------------------|--------------|------------|-----------|
| | Product name | CAS number | % |
| Form R - Reporting requirements | Methanol | 67-56-1 | ≥25 - <30 |
| Supplier notification | Methanol | 67-56-1 | ≥25 - <30 |

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

| Massachusetts | : The following components are listed: METHANOL; METHYL ALCOHOL |
|---------------|---|
| New York | : The following components are listed: Methanol |
| New Jersey | : The following components are listed: METHYL ALCOHOL; METHANOL |
| Pennsylvania | : The following components are listed: METHANOL |

California Prop. 65

WARNING: This product can expose you to Methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

| Ingredient name | | Maximum acceptable dosage level |
|-----------------|---|---------------------------------------|
| Methanol | - | Yes. |

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

| Australia | : All components are listed or exempted. |
|-------------------|--|
| Canada | : Not determined. |
| China | : All components are listed or exempted. |
| Europe | : All components are listed or exempted. |
| Japan | : Japan inventory (ENCS): All components are listed or exempted. Japan inventory (ISHL): All components are listed or exempted. |
| New Zealand | : All components are listed or exempted. |
| Philippines | : Not determined. |
| Republic of Korea | : Not determined. |
| Taiwan | : All components are listed or exempted. |

Section 15. Regulatory information

| Thailand | : Not determined. |
|---------------|--|
| Turkey | : All components are listed or exempted. |
| United States | : All components are active or exempted. |
| Viet Nam | : Not determined. |

Section 16. Other information

| <u>History</u> | |
|------------------------|---|
| Date of issue | : 11/20/2020 |
| Date of previous issue | : No previous validation |
| Version | : 1 |
| Key to abbreviations | : ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available UN = United Nations |

Procedure used to derive the classification

| Classification | Justification |
|---|-----------------------|
| FLAMMABLE LIQUIDS - Category 2 | On basis of test data |
| ACUTE TOXICITY (oral) - Category 4 | Calculation method |
| ACUTE TOXICITY (dermal) - Category 4 | Calculation method |
| ACUTE TOXICITY (inhalation) - Category 4 | Calculation method |
| SKIN IRRITATION - Category 2 | Calculation method |
| EYE IRRITATION - Category 2A | Calculation method |
| TOXIC TO REPRODUCTION - Category 1B | Calculation method |
| SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1 | Calculation method |
| SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract | Calculation method |
| irritation) - Category 3 | |
| SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - | Calculation method |
| Category 3 | |

V Indicates information that has changed from previously issued version.

Notice to reader

Disclaimer: The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.