

**PlusPore Columns** 

SAFETY DATA SHEET

### Section 1. Identification

This product is considered an article. This Safety Data Sheet is written based on the encapsulated substance or mixture in this article.

1.1 Product identifier	
Product name	: PlusPore Columns
Part no.	: PL1113-6520, PL1113-1320, PL1513-5520, PL1513-1320, PL1913-5520, PL1113-6325, PL1113-1325, PL1513-5325, PL1913-5325, PL1113-6300, PL1113-1300, PL1513-5300, PL1513-1300, PL1913-5300, PL1113-6500, PL1113-1500, PL1513-5500, PL1513-1500, PL1913-5500
Validation date	: 5/8/2021
1.2 Relevant identified uses	s of the substance or mixture and uses advised against
Material uses	: Malytical chemistry.         LC column         Solvent volume: < 10 mL         PL1113-6520       OligoPore 300 x 7.5 mm         PL1113-1320       OigoPore Guard 50 x 7.5 mm         PL1513-5520       OligoPore Guard 50 x 4.6 mm         PL1913-5520       OligoPore Guard 50 x 4.6 mm         PL1913-5520       OligoPore 2.1 x 250 mm         PL1113-6325       MesoPore 300 x 7.5 mm         PL1113-6325       MesoPore Guard 50 x 7.5 mm         PL1513-5325       MesoPore 250 x 4.6 mm         PL1913-5325       MesoPore 250 x 4.6 mm         PL1913-5325       MesoPore 2.1 x 250 mm         PL1113-6300       ResiPore 300 x 7.5 mm         PL1113-6300       ResiPore Guard 50 x 7.5 mm         PL1513-5300       ResiPore Guard 50 x 7.5 mm         PL1513-5300       ResiPore Guard 50 x 7.5 mm         PL1513-1300       ResiPore 250 x 4.6 mm         PL1913-5300       ResiPore 2.1 x 250 mm         PL1113-6500       PolyPore 300 x 7.5 mm         PL1113-6500       PolyPore 300 x 7.5 mm         PL1513-5500       PolyPore Guard 50 x 4.6 mm         PL1513-5500       PolyPore 250 x 4.6 mm         PL1513-5500       PolyPore Guard 50 x 7.5 mm         PL1513-5500       PolyPore Guard 50 x 4.6 mm     <

#### 1.3 Details of the supplier of the safety data sheet

Supplier/Manufacturer	: Agilent Technologies, Inc. 5301 Stevens Creek Blvd Santa Clara, CA 95051, USA 800-227-9770
	000-227-9770

#### **<u>1.4 Emergency telephone number</u>**

In case of emergency : CHEMTREC®: 1-800-424-9300

### Section 2. Hazards identification

This article, when used under reasonable conditions and in accordance with the directions for use, should not present a health hazard. The substance or mixture is encapsulated in the article. Only if released due to use or processing of the article in a manner not in accordance with the product's directions for use it may present potential health and safety hazards.

#### 2.1 Classification of the substance or mixture

**OSHA/HCS status** 

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Date of issue :	05/08/2021	1/13
-----------------	------------	------

# Section 2. Hazards identification

Classification of the substance or mixture		
H225	FLAMMABLE LIQUIDS - Category 2	
H332	ACUTE TOXICITY (inhalation) - Category 4	
H319	EYE IRRITATION - Category 2A	
H351	CARCINOGENICITY - Category 2	
H335	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3	
H336	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3	
H373	SPEČIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2	
H304	ASPIRATION HAZARD - Category 1	
Ingredients of unknown toxicity	<ul> <li>Percentage of the mixture consisting of ingredient(s) of unknown acute inhalation toxicity: 30 - 60%</li> </ul>	
	Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 37%	

2.2 GHS label elements	
Hazard pictograms	
Signal word	: Danger
Hazard statements	<ul> <li>H225 - Highly flammable liquid and vapor. H304 - May be fatal if swallowed and enters airways. H319 - Causes serious eye irritation. H332 - Harmful if inhaled. H335 - May cause respiratory irritation. H336 - May cause drowsiness or dizziness. H351 - Suspected of causing cancer. H373 - May cause damage to organs through prolonged or repeated exposure. (hearing organs)</li> </ul>
Precautionary statements	
Prevention	<ul> <li>P280 - Wear protective gloves, protective clothing and eye or face protection.</li> <li>P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</li> <li>P260 - Do not breathe vapor.</li> </ul>
Response	: ₱301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.
Storage	: ₱403 + P235 - Store in a well-ventilated place. Keep cool.
Disposal	<ul> <li>P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.</li> </ul>
2.3 Other hazards	
Hazards not otherwise classified	: None known.

# Section 3. Composition/information on ingredients

This article, when used under reasonable conditions and in accordance with the directions for use, should not present a health hazard. The substance or mixture is encapsulated in the article. Only if released due to use or processing of the article in a manner not in accordance with the product's directions for use it may present potential health and safety hazards.

Substance/mixture : Mixture (encapsulated in article)

Ingredient name	%	CAS number
ethylbenzene	≥50 - ≤69	100-41-4

Date of issue :	05/08/2021	2/1
-----------------	------------	-----

### Section 3. Composition/information on ingredients

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

1.1 Description of necessary first aid measures		
Eye contact	<ul> <li>Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.</li> </ul>	
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.	
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.	
Ingestion	: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.	

4.2 Most important sy	nptoms/effects, acute and delayed
Potential acute healt	<u>effects</u>
Eye contact	: Causes serious eye irritation.
Inhalation	: Farmful if inhaled. Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.
Over-exposure signs	symptoms
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
Skin contact	: No specific data.
Deter of the second second	- /00/0004

### Section 4. First aid measures

Ingestion	: Adverse symptoms may include the following: nausea or vomiting	
4.3 Indication of immediate	medical attention and special treatment needed, if necessary	
Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>	
Specific treatments	: No specific treatment.	
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.	

See toxicological information (Section 11)

### Section 5. Fire-fighting measures

5.1 Extinguishing media	
Suitable extinguishing media	: Use dry chemical, CO <sub>2</sub> , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet.
5.2 Special hazards arising	from the substance or mixture
Specific hazards arising from the chemical	: Fighly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide
5.3 Advice for firefighters	
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

# Section 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures			
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.	
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".	
6.2 Environmental precautions	:	Wooid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).	

### Section 6. Accidental release measures

6.3 Methods and materials for containment and cleaning up

- Methods for cleaning up
- : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

### Section 7. Handling and storage

### 7.1 Precautions for safe handling

Protective measures	: Fut on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
7.2 Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.
7.3 Specific end use(s) Recommendations	: Industrial applications, Professional applications.
Industrial sector specific solutions	: Not available.

### Section 8. Exposure controls/personal protection

Since the hazardous ingredient in this article is encapsulated, the risk of exposure by inhalation, ingestion, skin contact and eyes contact is minimum.

#### **8.1 Control parameters**

#### **Occupational exposure limits**

Ingredient name	Exposure limits		
ethylbenzene	ACGIH TLV (United States, 3/2020). TWA: 20 ppm 8 hours. OSHA PEL 1989 (United States, 3/1989).		
	TWA: 100 ppm 8 hours. TWA: 435 mg/m <sup>3</sup> 8 hours. STEL: 125 ppm 15 minutes. STEL: 545 mg/m <sup>3</sup> 15 minutes. <b>NIOSH REL (United States, 10/2016).</b> TWA: 100 ppm 10 hours. TWA: 435 mg/m <sup>3</sup> 10 hours.		

### Section 8. Exposure controls/personal protection

STEL: 125 ppm 15 minutes. STEL: 545 mg/m<sup>3</sup> 15 minutes. OSHA PEL (United States, 5/2018). TWA: 100 ppm 8 hours. TWA: 435 mg/m<sup>3</sup> 8 hours.

8.2 Exposure controls	
Appropriate engineering controls	: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measu	<u>ires</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear antistatic protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
Other skin protection	<ul> <li>Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

### Section 9. Physical and chemical properties

9.1 Information on	basic physical and chemical properties	
Appearance		
Physical state	: Solid. (containing flammable liquid)	
Color	: White.	
Odor	: Aromatic.	
Odor threshold	: Not available.	
Date of issue :	05/08/2021	6/13

# Section 9. Physical and chemical properties

рН	: Not available.
Melting point	: -95°C (-139°F)
Boiling point	: 136°C (276.8°F)
Flash point	: Closed cup: 21°C (69.8°F)
Evaporation rate	: Not available.
Flammability (solid, gas)	: Contains: Flammable liquid
Lower and upper explosive (flammable) limits	: Lower: 0.8% Upper: 6.7%
Vapor pressure	: Not available.
Vapor density	: Not available.
Relative density	: 0.9
Density	: 0.9 g/cm <sup>3</sup> [20°C (68°F)]
Solubility	: Mobile phase: Very slightly soluble in the following materials: water Stationary phase: Insoluble
Partition coefficient: n- octanol/water	: Not available.
Auto-ignition temperature	: 432.22°C (810°F)
Decomposition temperature	: Not available.
Viscosity	: Not available.

# Section 10. Stability and reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	The product is stable.
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
10.5 Incompatible materials	Reactive or incompatible with the following materials: oxidizing materials
10.6 Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products shoul not be produced.

### Section 11. Toxicological information

### 11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
efhylbenzene	LD50 Dermal LD50 Oral		>5000 mg/kg 3500 mg/kg	-

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
ethylbenzene	Eyes - Severe irritant Skin - Mild irritant	Rabbit Rabbit	-	500 mg 24 hours 15 mg	-

Date of issue :	05/08/2021	

### Section 11. Toxicological information

### Skin Sensitization

**Conclusion/Summary** 

: Repeated exposure may cause skin dryness or cracking.

#### Not available.

**Mutagenicity** 

Conclusion/Summary	: Not available.
--------------------	------------------

#### **Carcinogenicity**

**Conclusion/Summary** : Not available.

#### **Classification**

Product/ingredient name	OSHA	IARC	NTP
ethylbenzene	-	2B	-

#### Reproductive toxicity

**Conclusion/Summary** : Not available.

#### **Teratogenicity**

**Conclusion/Summary** : Not available.

#### Specific target organ toxicity (single exposure)

Name		Route of exposure	Target organs
ethylbenzene	Category 3	-	Respiratory tract irritation
	Category 3		Narcotic effects

#### Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
ethylbenzene	Category 2	-	hearing organs

#### Aspiration hazard

Name	Result
	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure	: Routes of entry anticipated: Oral, Dermal, Inhalation.
Potential acute health effect	<u>ts</u>
Eye contact	: Causes serious eye irritation.
Inhalation	: Farmful if inhaled. Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.
Symptoms related to the p	nysical, chemical and toxicological characteristics
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness

# Section 11. Toxicological information

Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
Skin contact	: No specific data.
Ingestion	<ul> <li>Adverse symptoms may include the following: nausea or vomiting</li> </ul>

#### Delayed and immediate effects and also chronic effects from short and long term exposure

<u>Short term exposure</u>		
Potential immediate effects	Not available.	
Potential delayed effects	Not available.	
Long term exposure		
Potential immediate effects	Not available.	
Potential delayed effects	Not available.	
Potential chronic health eff	<u>s</u>	
General	May cause damage to organs through prolonged or repeated exposure.	
Carcinogenicity	Suspected of causing cancer. Risk of cancer depends on duration and leve exposure.	l of
Mutagenicity	No known significant effects or critical hazards.	
Reproductive toxicity	No known significant effects or critical hazards.	

### Numerical measures of toxicity

### Acute toxicity estimates

Product/ingredient name		(mg/kg)	(gases)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/ I)
PlusPore Columns	5555.6		N/A	11	N/A
ethylbenzene	3500		N/A	11	N/A

# Section 12. Ecological information

### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
ethylbenzene	Acute EC50 4600 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 3600 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
	Acute EC50 6.53 mg/l Marine water	Crustaceans - Artemia sp Nauplii	48 hours
	Acute EC50 2.93 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 4200 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours

# Section 12. Ecological information

12.2 Persistence and degrad	<u>ability</u>					
Product/ingredient name	Test	Result		Dose		Inoculum
ethylbenzene	ISO	70 to 80 %	- Readily - 28 days	-		Activated sludge
Product/ingredient name	Aquatic half-life		Photolysis		Biodeg	radability
ethylbenzene	-		-		Readily	

#### **12.3 Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
ethylbenzene	3.6	-	low

#### 12.4 Mobility in soil

Soil/water partition: Not available.coefficient (Koc)

**12.5 Other adverse effects** : No known significant effects or critical hazards.

### Section 13. Disposal considerations

#### **13.1 Waste treatment methods**

**Disposal methods** 

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.

The information presented below only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

### Section 14. Transport information

This Safety Data Sheet is written based on the encapsulated substance or mixture in this article. Since the hazardous ingredient is encapsulated, the risk of exposure by inhalation, ingestion, skin contact and eyes contact is minimum.

DOT / TDG / Mexico / IMDG / : Not regulated. IATA Additional information

# Section 14. Transport information

<b>Remarks</b> : Special provisions
DOT: 47
TDG: 56
MX: 216
IATA: A46
IMDG: 216

Special precautions for user	1	Transport within user's premises: always transport in closed containers that are
		upright and secure. Ensure that persons transporting the product know what to do in the
		event of an accident or spillage.

Transport in bulk according : Not available. to IMO instruments

### Section 15. Regulatory information

15.1 Safety, health and envi	onmental regulations/legislation specific for the substance or mixture
U.S. Federal regulations	: TSCA 8(a) CDR Exempt/Partial exemption: Not determined Clean Water Act (CWA) 307: ethylbenzene Clean Water Act (CWA) 311: ethylbenzene
Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)	: Listed
Clean Air Act Section 602 Class I Substances	: Not listed
Clean Air Act Section 602 Class II Substances	: Not listed
DEA List I Chemicals (Precursor Chemicals)	: Not listed
DEA List II Chemicals (Essential Chemicals)	: Not listed
<u>SARA 302/304</u>	
Composition/information	on ingredients
No products were found.	
SARA 304 RQ	: Not applicable.
<u>SARA 311/312</u>	
Classification	<ul> <li>LAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY (inhalation) - Category 4 EYE IRRITATION - Category 2A CARCINOGENICITY - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 ASPIRATION HAZARD - Category 1</li> </ul>
Composition/information	on ingredients

**Composition/information on ingredients** 

### Section 15. Regulatory information

Name	%	Classification
<b>e</b> thylbenzene	≥50 - ≤69	FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY (inhalation) - Category 4 EYE IRRITATION - Category 2A CARCINOGENICITY - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 ASPIRATION HAZARD - Category 1 HNOC - Defatting irritant HNOC - Static-accumulating flammable liquid

#### **SARA 313**

	Product name	CAS number	%
Form R - Reporting requirements	ethylbenzene	100-41-4	≥50 - ≤69
Supplier notification	ethylbenzene	100-41-4	≥50 - ≤69

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

#### **State regulations**

**Massachusetts** 

Pennsylvania

: The following components are listed: ETHYL BENZENE; ETHYLBENZENE

**New York** 

- : The following components are listed: Ethylbenzene
- New Jersey
- : The following components are listed: ETHYL BENZENE; BENZENE, ETHYL-
- : The following components are listed: BENZENE, ETHYL-

#### California Prop. 65

**WARNING**: This product can expose you to Ethylbenzene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
Fthylbenzene	Yes.	-

#### International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals Not listed.

#### **Montreal Protocol**

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

#### Inventory list

Australia	1	All components are listed or exempted.
Canada	:	All components are listed or exempted.

- China : All components are listed or exempted.
- **Europe** : All components are listed or exempted.

|--|

### Section 15. Regulatory information

Japan	: Japan inventory (ENCS): All components are listed or exempted. Japan inventory (ISHL): All components are listed or exempted.
New Zealand	: All components are listed or exempted.
Philippines	: All components are listed or exempted.
Republic of Korea	: All components are listed or exempted.
Taiwan	: All components are listed or exempted.
Thailand	: Not determined.
Turkey	: All components are listed or exempted.
United States	: 🕅 components are active or exempted.
Viet Nam	: 🕅 components are listed or exempted.

# Section 16. Other information

<u>History</u>	
Date of issue	: 05/08/2021
Date of previous issue	: 09/10/2018
Version	: 5
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available UN = United Nations

Procedure used to derive the classification

Classification	Justification
AMMABLE LIQUIDS - Category 2	On basis of test data
ACUTE TOXICITY (inhalation) - Category 4	Calculation method
EYE IRRITATION - Category 2A	Calculation method
CARCINOGENICITY - Category 2	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3	Calculation method
SPEČIFÍC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 ASPIRATION HAZARD - Category 1	Calculation method Expert judgment

**V** Indicates information that has changed from previously issued version.

#### Notice to reader

Disclaimer: The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.