Conforms to US OSHA Hazard Communication 29CFR1910.1200

SAFETY DATA SHEET



Poroshell HPH-C18 Chromatography Columns with Acetonitrile and Water less than 10mL

Section 1. Identification

This product is considered an article. This Safety Data Sheet is written based on the encapsulated substance or mixture in this article.

1.1 Product identifier	
Product name	 Poroshell HPH-C18 Chromatography Columns with Acetonitrile and Water less than 10mL
Part no.	: \$93775-702, 693975-502, 693975-702, 695775-702, 695975-502, 695975-702, 699775-702, 699975-502, 699975-702, 821725-930, 699770-702, 695770-702, 693770-702, 690770-702, 823750-930, 699970-502, 695970-502, 693970-502, 690970-502, 820750-930, 699970-702, 695970-702, 693970-702, 690970-702, 820750-928, 823750-928, 821725-928, 690770-702T, 690970-502T, 690970-702T, 693770-702T, 693775-702T, 693970-502T, 693970-702T, 693975-502T, 693975-702T, 695770-702T, 695775-702T, 695970-502T, 695970-702T, 695975-502T, 699975-702T, 699770-702T, 699775-702T, 699970-502T, 699970-702T, 699975-502T, 699975-702T, 699675-702, 695675-702, 693675-702, 695675-502, 695675-502, 821725-945, 823750-945, 691775-502, 695775-502
Validation date	: 6/9/2021
1.2 Relevant identified uses	of the substance or mixture and uses advised against
Material uses	: Analytical chemistry.
	chromatography column
	Solvent volume: < 10 mL 693775-702 Poroshell HPH-C18, 2.1 x 150 mm, 2.7 um
	693975-502 Poroshell HPH-C18, 3.0 x 150 mm, 2.7 um
	693975-702 Poroshell HPH-C18, 4.6 x 150 mm, 2.7 um
	695775-702 Poroshell HPH-C18, 2.1 x 100 mm, 2.7 um
	695975-502 Poroshell HPH-C18, 3.0 x 100 mm, 2.7 um
	695975-702 Poroshell HPH-C18, 4.6 x 100 mm, 2.7 um
	699775-702 Poroshell HPH-C18, 2.1 x 50 mm, 2.7 um
	699975-502 Poroshell HPH-C18, 3.0 x 50 mm, 2.7 um
	699975-702 Poroshell HPH-C18, 4.6 x 50 mm, 2.7 um 821725-930 Poroshell HPH-C18, 2.1 x 5 mm, 4 um
	699770-702 Poroshell HPH-C18, 2.1 x 50 mm, 4 um
	695770-702 Poroshell HPH-C18, 2.1 x 100 mm, 4 um
	693770-702 Poroshell HPH-C18, 2.1 x 150 mm, 4 um
	690770-702 Poroshell HPH-C18, 2.1 x 250 mm, 4 um
	823750-930 Poroshell HPH-C18, 3 x 5 mm, 4 um
	699970-502 Poroshell HPH-C18, 3 x 50 mm, 4 um
	695970-502 Poroshell HPH-C18, 3 x 100 mm, 4 um
	693970-502 Poroshell HPH-C18, 3 x 150 mm, 4 um 690970-502 Poroshell HPH-C18, 3 x 250 mm, 4 um
	690970-502 Poroshell HPH-C18, 3 x 250 mm, 4 um 820750-930 Poroshell HPH-C18, 4.6 x 5 mm, 4 um
	699970-702 Poroshell HPH-C18, 4.6 x 50 mm, 4 um
	695970-702 Poroshell HPH-C18, 4.6 x 100 mm, 4 um
	693970-702 Poroshell HPH-C18, 4.6 x 150 mm, 4 um
	690970-702 Poroshell HPH-C18, 4.6 x 250 mm, 4 um
	820750-928 UHPLC Grd, Poroshell HPH-C18, 4.6 mm, 3 pk
	823750-928 UHPLC Grd, Poroshell HPH-C18, 3.0 mm, 3 pk
	821725-928 UHPLC Grd, Poroshell HPH-C18, 2.1 mm, 3 pk
	690770-702T Poroshell HPH-C18, 2.1x 250mm, 4um, T 690970-502T Poroshell HPH-C18, 3x 250mm, 4um, T
	690970-702T Poroshell HPH-C18, 4.6x 250mm, 4um, T
	693770-702T Poroshell HPH-C18, 2.1x 150mm, 4um, T
	693775-702T Poroshell HPH-C18, 2.1 x 150mm, 2.7um, T
	693970-502T Poroshell HPH-C18, 3 x 150mm, 4um, T
	693970-702T Poroshell HPH-C18, 4.6 x 150mm, 4um, T
	693975-502T Poroshell HPH-C18, 3 x 150mm, 2.7um, T
	693975-702T Poroshell HPH-C18, 4.6 x 150mm, 2.7um, T

Section 1. Identification

695770-702T	Poroshell HPH-C18, 2.1 x 100mm, 4um, T
695775-702T	Poroshell HPH-C18, 2.1 x 100mm, 2.7um, T
695970-502T	Poroshell HPH-C18, 3 x 100mm, 4um, T
695970-702T	Poroshell HPH-C18, 4.6 x 100mm, 4um, T
695975-502T	Poroshell HPH-C18, 3 x 100mm, 2.7um, T
695975-702T	Poroshell HPH-C18, 4.6 x 100mm, 2.7um, T
699770-702T	Poroshell HPH-C18, 2.1 x 50mm, 4um, T
699775-702T	Poroshell HPH-C18, 2.1 x 50mm, 2.7um, T
699970-502T	Poroshell HPH-C18, 3 x 50mm, 4um, T
699970-702T	Poroshell HPH-C18, 4.6 x 50mm, 4um, T
699975-502T	Poroshell HPH-C18, 3 x 50mm, 2.7um, T
699975-702T	Poroshell HPH-C18, 4.6 x 50mm, 2.7um, T
699675-702	Poroshell HPH-C18,2.1x50mm,1.9um,T
695675-702	Poroshell HPH-C18,2.1x100mm,1.9um,T
693675-702	Poroshell HPH-C18,2.1x150mm,1.9um,T
699675-502	Poroshell HPH-C18,3x50mm,1.9um,T
695675-502	Poroshell HPH-C18,3x100mm,1.9um,T
693675-502	Poroshell HPH-C18,3x150mm,1.9um,T
821725-945	UHPLC Grd,P120 HPH-C18,2.1mm,1.9um,3pk
823750-945	UHPLC Grd,P120 HPH-C18,3mm,1.9um,3pk
691775-502	Poroshell 120, HPH-C18, 3.0x30mm, 1.9um, T
695775-502	Poroshell 120, HPH-C18, 2.1x30mm, 1.9um, T

1.3 Details of the supplier of the safety data sheet

Supplier/Manufacturer	: Agilent Technologies, Inc. 5301 Stevens Creek Blvd
	Santa Clara, CA 95051, USA
	800-227-9770

1.4 Emergency telephone number

In case of emergency

: CHEMTREC®: 1-800-424-9300

Section 2. Hazards identification

This article, when used under reasonable conditions and in accordance with the directions for use, should not present a health hazard. The substance or mixture is encapsulated in the article. Only if released due to use or processing of the article in a manner not in accordance with the product's directions for use it may present potential health and safety hazards.

2.1 Classification of the substance or mixture

OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the sub	stance or mixture
₩225 H319 H373	FLAMMABLE LIQUIDS - Category 2 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
2.2 GHS label elements Hazard pictograms	

Signal word
Hazard statements

: Danger

- : H225 Highly flammable liquid and vapor.
 - H319 Causes serious eye irritation.

H373 - May cause damage to organs through prolonged or repeated exposure. (blood system, central nervous system (CNS), kidneys, liver)

Poroshell HPH-C18 Chromatography Columns with Acetonitrile and Water less than 10mL

Section 2. Hazards identification

Precautionary statements	
Prevention	 P280 - Wear eye or face protection. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P260 - Do not breathe vapor.
Response	: P314 - Get medical advice or attention if you feel unwell.
Storage	: 🗗 403 + P235 - Store in a well-ventilated place. Keep cool.
Disposal	 P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
2.3 Other hazards	
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

This article, when used under reasonable conditions and in accordance with the directions for use, should not present a health hazard. The substance or mixture is encapsulated in the article. Only if released due to use or processing of the article in a manner not in accordance with the product's directions for use it may present potential health and safety hazards.

Substance/mixture : **M**ixture (encapsulated in article)

Ingredient name	%	CAS number
Acetonitrile	≥10 - <22	75-05-8

Contains: Organosilane bonded silica gel.

Note: To the best of our knowledge, the acute and chronic toxicological properties of bonded silica gels have not been investigated. This product contains synthetic amorphous silica, and should not be confused with crystalline silica such as quartz, cristobalite, or tridymite, or with diatomaceous earth or other naturally occurring forms of amorphous silica that frequently contain crystalline forms of silica.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

4.1 Description of necessary first aid measures

Eye contact	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention following exposure or if feeling unwell. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention following exposure or if feeling unwell. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Section 4. First aid measures

Ingestion	: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention following exposure or if feeling unwell. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
4.2 Most important symptor	ns/effects, acute and delayed
Potential acute health effe	<u>cts</u>
Eye contact	: Causes serious eye irritation.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
<u>Over-exposure signs/symp</u>	<u>otoms</u>
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.
4.3 Indication of immediate	medical attention and special treatment needed, if necessary
Notes to physician	 In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.
See toxicological informatio	on (Section 11)

Section 5. Fire-fighting measures

: Use dry chemical, CO ₂ , water spray (fog) or foam.
: Do not use water jet.
from the substance or mixture
: Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides cyanides

Section 5. Fire-fighting measures

5.3 Advice for firefighters		
Special protective actions for fire-fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

6.1 Personal precautions, pro	tective equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
6.3 Methods and materials fo	r containment and cleaning up

Methods for cleaning up Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

7.1 Precautions for safe handling

7.2 Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Protective measures	: Put on appropriate personal protective equipment (see Section 8). Do not breathe vapor or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Section 7. Handling and storage

7.3 Specific end use(s)

Recommendations

: Industrial applications, Professional applications.

Industrial sector specific solutions

: Not available.

Section 8. Exposure controls/personal protection

Since the hazardous ingredient in this article is encapsulated, the risk of exposure by inhalation, ingestion, skin contact and eyes contact is minimum.

8.1 Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Acetonitrile	ACGIH TLV (United States, 3/2020). Absorbed through skin. TWA: 20 ppm 8 hours. OSHA PEL 1989 (United States, 3/1989). TWA: 40 ppm 8 hours. TWA: 70 mg/m ³ 8 hours. STEL: 60 ppm 15 minutes. STEL: 105 mg/m ³ 15 minutes. NIOSH REL (United States, 10/2016). TWA: 20 ppm 10 hours. TWA: 34 mg/m ³ 10 hours. OSHA PEL (United States, 5/2018). TWA: 40 ppm 8 hours. TWA: 70 mg/m ³ 8 hours.

8.2 Exposure controls	
Appropriate engineering controls	: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation o other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measu	<u>S</u>
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection	

Section 8. Exposure controls/personal protection

Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

9.1 Information on basic physical and chemical properties				
<u>Appearance</u>				
Physical state	: Solid. (containing flammable liquid)			
Color	: Not available.			
Odor	: Not available.			
Odor threshold	: Not available.			
рН	: Not available.			
Melting point	: Not available.			
Boiling point	: Not available.			
Flash point	: Closed cup: -18 to 23°C (-0.4 to 73.4°F)			
Evaporation rate	: Not available.			
Flammability (solid, gas)	: Contains: Flammable liquid			
Lower and upper explosive (flammable) limits	: Not available.			
Vapor pressure	: Not available.			
Vapor density	: Not available.			
Relative density	: Not available.			
Solubility	: Stationary phase: Insoluble Mobile phase: Soluble			
Partition coefficient: n- octanol/water	: Not available.			
Auto-ignition temperature	: Not available.			
Decomposition temperature	: Not available.			
Viscosity	: Not available.			

Section 10. Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
10.5 Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials Incompatible with hydrogen fluoride.
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Acetonitrile	LC50 Inhalation Vapor LD50 Oral		17100 ppm 2460 mg/kg	4 hours -

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Acetonitrile	Eyes - Moderate irritant	Rabbit	-	24 hours 100 uL	-
	Skin - Mild irritant	Rabbit	-	500 mg	-

Sensitization

Not available.

Mutagenicity

Conclusion/Summary	: Not available.		
Carcinogenicity			
Conclusion/Summary	: Not available.		
Reproductive toxicity			
Conclusion/Summary	: Not available.		
Teratogenicity			
Conclusion/Summary	: Not available.		
Specific target organ toxicity (single exposure)			

Not available.

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
Kcetonitrile	Category 2		blood system, central nervous system (CNS), kidneys, liver

Aspiration hazard

Date of issue :	06/09/2021	8/1	13
-----------------	------------	-----	----

Section 11. Toxicological information

Not available.

Information on the likely routes of exposure	Routes of entry anticipated: Oral, Dern	nal, Inhalation.
Potential acute health effect		
Eye contact	Causes serious eye irritation.	
Inhalation	No known significant effects or critical	hazards.
Skin contact	No known significant effects or critical	hazards.
Ingestion	No known significant effects or critical	hazards.
Symptoms related to the phy	al, chemical and toxicological charad	<u>cteristics</u>
Eye contact	Adverse symptoms may include the fol pain or irritation watering redness	lowing:

reaness
: No specific data.
: No specific data.
: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
<u>Long term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health eff	<u>ects</u>
General	: May cause damage to organs through prolonged or repeated exposure.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

	Dermal (mg/kg)		Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/ I)
2384.4 500	5245.6 1100	N/A N/A	52.5 11	N/A N/A
	kg)	kg) (mg/kg) 2384.4 5245.6	kg) (mg/kg) (gases) (ppm) 2384.4 5245.6 N/A	kg) (mg/kg) (gases) (ppm) (vapors) (mg/l) 2384.4 5245.6 N/A 52.5

Section 12. Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Acetonitrile	Acute LC50 1000000 µg/l Fresh water Chronic NOEC 1000000 µg/l Fresh water	Aquatic plants - Lemna minor Daphnia - Daphnia magna Fish - Pimephales promelas Aquatic plants - Lemna minor Daphnia - Daphnia magna	96 hours 48 hours 96 hours 96 hours 21 days

12.2 Persistence and degradability

Product/ingredient name	Test	Result		Dose		Inoculum
Acetonitrile	OECD 310 Ready Biodegradability - CO ₂ in Sealed Vessels (Headspace Test)		dily - 21 days	-		Activated sludge
Product/ingredient name	Aquatic half-life		Photolysis	·	Biodeg	radability
Acetonitrile	-		-		Readily	

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Acetonitrile	-0.34	3	low

12.4 Mobility in soil

Soil/water partition : Not available. coefficient (Koc)

12.5 Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

13.1 Waste treatment methods

Disposal methods	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
------------------	---

United States - RCRA Toxic hazardous waste "U" List

Ingredient	CAS #		Reference number
Acetonitrile (I,T)	75-05-8	Listed	U003

Poroshell HPH-C18 Chromatography Columns with Acetonitrile and Water less than 10mL

Section 13. Disposal considerations

Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.

The information presented below only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

Section 14. Transport information

This Safety Data Sheet is written based on the encapsulated substance or mixture in this article. Since the hazardous ingredient is encapsulated, the risk of exposure by inhalation, ingestion, skin contact and eyes contact is minimum.

DOT / TDG / Mexico / IMDG / : Not regulated.

ΙΑΤΑ

Additional information

Remarks: Special provisions DOT: 47 TDG: 56 MX: 216 IATA: A46 IMDG: 216

U.S. Endoral regulations

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to IMO instruments

Section 15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- TSCA 9(a) DAID: Apotopitrila

U.S. Federal regulations	 ISCA 8(a) PAIR: Acetonitrile TSCA 8(a) CDR Exempt/Partial exemption: Not determined Clean Water Act (CWA) 307: Acetonitrile
Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)	: Listed
Clean Air Act Section 602 Class I Substances	: Not listed
Clean Air Act Section 602 Class II Substances	: Not listed
DEA List I Chemicals (Precursor Chemicals)	: Not listed
DEA List II Chemicals (Essential Chemicals)	: Not listed
SARA 302/304 Composition/information	on ingredients

Section 15. Regulatory information

No products were found.

SARA 304 RQ

: Not applicable.

- SARA 311/312
- Classification

: FLAMMABLE LIQUIDS - Category 2 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2

Composition/information on ingredients

Name	%	Classification
Ørganosilane bonded silica gel Acetonitrile	≥50 - ≤75 ≥10 - <22	COMBUSTIBLE DUSTS FLAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (dermal) - Category 4 ACUTE TOXICITY (inhalation) - Category 4 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	Acetonitrile	75-05-8	≥10 - <22
Supplier notification	Acetonitrile	75-05-8	≥10 - <22

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts	: The following components are listed: ACETONITRILE
New York	: The following components are listed: Acetonitrile; Ethanenitrile
New Jersey	: The following components are listed: ACETONITRILE; CYANOMETHANE
Pennsylvania	: The following components are listed: ACETONITRILE
<u>California Prop. 65</u>	

This product does not require a Safe Harbor warning under California Prop. 65.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC) Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Australia	: All components are listed or exempted.
Canada	: Not determined.
China	: All components are listed or exempted.
Europe	: All components are listed or exempted.

Date of issue :	06/09/2021	12/	′13
-----------------	------------	-----	-----

Section 15. Regulatory information

Japan	 Japan inventory (ENCS): All components are listed or exempted. Japan inventory (ISHL): All components are listed or exempted.
New Zealand	: All components are listed or exempted.
Philippines	: Not determined.
Republic of Korea	: Not determined.
Taiwan	: All components are listed or exempted.
Thailand	: Not determined.
Turkey	: All components are listed or exempted.
United States	: 🕅 components are active or exempted.
Viet Nam	: Not determined.

Section 16. Other information

Н	is	to	ry	

Date of issue	: 06/09/2021
Date of previous issue	: 10/14/2019
Version	: 6
Key to abbreviations	 ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available UN = United Nations

Procedure used to derive the classification

Classification	Justification
· · · · · · · · · · · · · · · · · · ·	On basis of test data
EYE IRRITATION - Category 2A	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2	Calculation method

V Indicates information that has changed from previously issued version.

Notice to reader

Disclaimer: The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.